



Important

The domain property is case sensitive; so i2b2*D*emo is not the same as i2b2*d*emo.

3. Update *jbosHost:jbosPort* with the name of your WildFly host and its port.



Steps to update Workbench properties for multiple domains

If you have more than one environment you can include all of them in this one properties file by doing the following.

1. Copy the string you just edited to a new line.
2. Update the domain and WildFly information with the correct information for the additional hive.
3. Make sure you advance the number at the beginning of the string ("i2b2.2").

Example:

i2b2workbench.properties

```

i2b2.1=i2b2demo,REST,http://services.i2b2.org/i2b2/services/PMService/
i2b2.2=i2b2demo,REST,http://localhost:9090/i2b2/services/PMService/
i2b2.3=TestDomain,REST,http://myTestWildFly .org:myTestWildFly Port/i2b2/services/PMService/
i2b2.4=ProdDomain,REST,http://myProdWildFly .org:myProdWildFly Port/i2b2/services/PMService/

```



Tip

If you do not want users to see the i2b2demo domain that was delivered with the i2b2 Workbench you can either remove it or comment it out by placing a pound sign (#) in front of the string.

Also, the last domain listed in the properties file will be the one that defaults at the **Target location** when logging into the i2b2 Workbench. We recommend the domain users log into the most be the last one listed in your properties file.



