

Logic Workflow

In this example walkthrough you will see how to set up a SHRINE i2b2 user with the correct roles, and set up for Active Directory Sync by calling the web services of the PM Cell.

| Step | Logic | PHP | XML | Example PHP Call |
|------|--|-------------------------------|---|---|
| 1 | Check that a user is not already registered in SHRINE project | <code>get_role()</code> | <code><pm: get_role></code> | <pre>i2b2_get_role(\$user_name,\$config_start_project_id)</pre> |
| 2 | Set the user in the i2b2 SHRINE project | <code>set_user()</code> | <code><pm: set_user></code> | <pre>i2b2_set_user(\$user_name, \$full_name, \$email, "", "")</pre> |
| 3 | Give the user role of DATA_AGG | <code>set_role()</code> | <code><pm: set_role></code> | <pre>i2b2_set_role(\$user_name, 'DATA_AGG', \$config_start_project_id)</pre> |
| 4 | Give the user role of USER | <code>set_role()</code> | <code><pm: set_role></code> | <pre>i2b2_set_role(\$user_name, 'USER', \$config_start_project_id)</pre> |
| 5 | Set the user param of authentication_method to NTLM | <code>set_user_param()</code> | <code><pm: set_user_param></code> | <pre>i2b2_set_user_param(\$user_name, "authentication_method", "T", "NTLM")</pre> |
| 6 | Set the user param of domain to your AD domain | <code>set_user_param()</code> | <code><pm: set_user_param></code> | <pre>i2b2_set_user_param(\$user_name, "domain", "T", \$config_AD_Domain)</pre> |
| 7 | Set the user param of domain_controller to the address of your domain controller | <code>set_user_param()</code> | <code><pm: set_user_param></code> | <pre>i2b2_set_user_param(\$user_name, "domain_controller", "T", \$config_domain_controller)</pre> |