

# WORK QRY.xsd

WORK\_QRY.xsd

<b>&lt;request&gt;</b>	<b>Container for request information</b>

<b>&lt;folders&gt;</b>	<b>Container list of folders returned in a response</b>

<b>&lt;folder&gt;</b>	<b>Container for a folder returned in a response; an object that holds information from rows in a WORKPLACE table.</b>
<b>&lt;name&gt;</b>	The name of the workplace item.
<b>&lt;index&gt;</b>	A "table code\unique index" pair. Example: \\i2b2\1 In the above example, "i2b2" equates to the table code and a unique index of "1".
<b>&lt;parentIndex&gt;</b>	The index of the parent of this workplace item.
<b>&lt;visualAttributes&gt;</b>	Three character string that indicates the graphical representation of the term. Example: String XYZ, where X can be "C" (container), "F" (folder), "L" (leaf), "M" (multi) Y can be "A" (active), "I" (inactive), "H" (hidden) Z can be "O" (open) or null
<b>&lt;tooltip&gt;</b>	A tooltip that is associated with the workplace item.
<b>&lt;groupID&gt;</b>	The project or group ID associated with the workplace item.
<b>&lt;shareID&gt;</b>	Indicates whether or not the workplace item is shared (Y/N).
<b>&lt;statusCd&gt;</b>	Indicates the status of the workplace item ("D" = deleted).
<b>&lt;userID&gt;</b>	The user ID of the originator of the workplace item.
<b>&lt;workXmlSchema&gt;</b>	The schema associated with <workXml>.
<b>&lt;workXmlI2B2Type&gt;</b>	The i2b2 type associated with the drag and drop XML.