

GIRI Home

GIRI (Generic integration of R into i2b2)

Author: [Bastian Weinlich](#)

Short Description

The project follows a similar goal as the "[R Engine Cell](#)" of the University of Pavia and [rgate \(HERON\)](#) of the University of Kansas: To make arbitrary R functions available within i2b2. In contrast to these approaches, it is very simple to add new statistical functionality with GIRI. To do so, it is sufficient to write an R script and an optional XML configuration file to add what is known as a "Scriptlet" (a kind of an addon) that comprises one or more R functions. In particular, it is not necessary to implement an i2b2 webclient plugin for every newly added scriptlet individually. The end user simply selects the desired scriptlet from a drop down list from a generic i2b2 webclient plugin and has then several options to customize the input data (e.g. drag and drop patient sets / concepts). Afterwards, he clicks on "View Results" to start computations. The following results page can - depending on the scriptlet - consist of numerical / textual values, tables and plots. Additionally, all data can be exported as files.


Examples

A simple scriptlet could compute two quantiles of age from a previously selected patient set. The end user can define the p values. Here is a step-by-step guide to using the scriptlet:

Specify the input data:

The screenshot shows the GIRIPlugin web interface. At the top, there are tabs for 'Choose scriptlet', 'View Results', and 'Help'. Below the tabs, a dropdown menu is set to 'Quantiles of age'. To the right of the dropdown, a note says 'Choose between several previously written scriptlets'. Below the dropdown, the title 'Quantiles of age' is displayed. Underneath, a prompt says 'Please select a patient set and fill in two values for p.' The 'Drag and drop fields:' section contains a red button labeled 'Click here to drag fields...', a green box labeled 'Circula-Male@19:51:46 [4]', a blue box labeled 'Concept 1', and a blue box labeled 'Patient Set 2'. To the right of this section, a note says 'Define input data by dragging and dropping patient sets and concepts'. Below this, the 'Additional input settings' section is shown. It has two input fields for 'p' values. The first is labeled 'p for lower quantile' with a note 'Fill in a numeric value between 0.0 and 1.0, e.g. 0.05' and contains the value '0.02'. The second is labeled 'p for upper quantile' with a note 'Fill in a numeric value between 0.0 and 1.0, e.g. 0.95' and contains the value '0.98'. To the right of these fields, a note says 'Type in additional parameters to customize the computation'.

Afterwards click on "View Results" to start the computation:



The scriptlet consists of two files that have to be stored on the server where the GIRI Cell is running. The first one is the R script including the following R code:

mainscript.r

```
GIRI.output["Lower quantile"] <- quantile(GIRI.patients[[1]]$age_in_years_num, as.numeric(GIRI.input[["p for lower quantile"]]))
GIRI.output["Upper quantile"] <- quantile(GIRI.patients[[1]]$age_in_years_num, as.numeric(GIRI.input[["p for upper quantile"]]))
boxplot(GIRI.patients[[1]]$age_in_years_num, horizontal=T)
```

Accessing input and output is possible by using special naming conventions (GIRI.patients, GIRI.input, GIRI.output...). Plots are always displayed.

The second file configures the R scriptlet through XML code:

config.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<giriconf:Rscriptlet xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:giriconf="http://www.i2b2.org/xsd/cell/giriconf/1.0/">
  <settings>
    <title>Quantiles of age</title>
    <description>Please select a patient set and fill in two values for p.</description>
    <passROutput>false</passROutput>
    <passRErrors>true</passRErrors>
    <plotDescription>Here you can see a boxplot of the patient's ages:</plotDescription>
  </settings>
  <additionalInputs>
    <input>
      <name>p for lower quantile</name>
      <description>Fill in a numeric value between 0.0 and 1.0, e.g. 0.05</description>
      <type>text</type>
      <lines>1</lines>
    </input>
    <input>
      <name>p for upper quantile</name>
      <description>Fill in a numeric value between 0.0 and 1.0, e.g. 0.95</description>
      <type>text</type>
      <lines>1</lines>
    </input>
  </additionalInputs>
  <customOutputs>
    <output>
      <name>Lower quantile</name>
      <description>This is the lower quantile. It describes the value where (p * number of
patients) lies below this value.</description>
    </output>
    <output>
      <name>Upper quantile</name>
      <description>This is the upper quantile. It describes the value where (p * number of
patients) lies above this value.</description>
    </output>
  </customOutputs>
</giriconf:Rscriptlet>
```

Settings, input variables and outputs are defined in this configuration file. For more information about creating scriptlets see the [notes for scriptlet developers](#).

The following slide show depicts a scriptlet that computes a Kaplan Meier plot:

Kaplan Meier Example

