3.6.2 Set Database Properties

Step 2: Set Database Properties for Imdata Tables

As stated earlier each i2b2 database schema has a corresponding directory that contains the data files for installing the data. Each of these directories has a file called **db.properties** and it needs to be updated with your environment variables.

Steps for setting database properties

Assumptions:

- You are logged into the command line application for your environment. *(Linux: Terminal or Shell and Windows: Command Prompt)*
- You have already changed your working directory to the one that is appropriate for this installation.

1. At the command prompt type the following:

Linux Command
open db.properties

Windows Command
db.properties

2. The **db.properties** file will open. Set the following properties for the DBMS at your site:

> **Important**
>
> When setting the database properties make sure you set the user to **i2b2imdata** and the project to **demo**.

Database Properties File

Oracle Database

```
db.type=oracle
db.username=i2b2imdata
db.password=demouser
db.server=LocationOfYourDatabase:1521:xe
db.driver=oracle.jdbc.driver.OracleDriver
db.url=jdbc:oracle:thin:@LocationOfYourDatabase:1521:xe
db.project=demo
```

PostgreSQL Database

```
db.type=postgresql
db.username=i2b2imdata
db.password=demouser
db.driver=org.postgresql.Driver
db.url=jdbc:postgresql://LocationOfYourDatabase/i2b2?searchpath=i2b2imdata
db.project=demo
```

SQL Server Database

```
db.type=sqlserver
db.username=i2b2imdata
db.password=demouser
db.driver=com.microsoft.sqlserver.jdbc.SQLServerDriver
db.url=jdbc:sqlserver://LocationOfYourDatabase:1433;database=demo
db.project=demo
```

3. Save the changes and close the file.

Tip

To save yourself steps, DO NOT close your Command Prompt window as you will be continuing to use it throughout the remainder of the installation.