

10.4.4.1.3 Ontology Cell Properties

Step 9: CRC properties: Configure ONT cell properties

In order for the CRC to communication with the Ontology cell the following properties need to be modified to reflect you environment.

1. In the **crc.properties** file scroll to the section called **Ontology Cell**.
2. Edit the **queryprocessor.ws.ontology.url** and **edu.harvard.i2b2.crc.delegate.ontology.url** properties to reflect the location of the Ontology cell in your environment.



Important

When you edit the **queryprocessor.ws.ontology.url** and **edu.harvard.i2b2.crc.delegate.ontology.url** properties with the location of your Ontology Cell it is ***extremely important*** that you only edit the **hostname** (*local/host*) and the **port** (*9090*). The remainder of the URL is required as it is written and should not be changed.

Ontology Cell

```
queryprocessor.ws.ontology.url=http://local/host:9090/i2b2/services/OntologyService/getTermInfo  
edu.harvard.i2b2.crc.delegate.ontology.url=http://local/host:9090/i2b2/services/OntologyService  
edu.harvard.i2b2.crc.delegate.ontology.operation.getterminfo=/getTermInfo  
edu.harvard.i2b2.crc.delegate.ontology.operation.getchildren=/getChildren  
edu.harvard.i2b2.crc.delegate.ontology.operation.getmodifierinfo=/getModifierInfo
```

3. Save your changes but do not close the file. You will be continuing to edit the file in the next few sections.