

12.4.2 Configure the FR Application Directory Properties

Step 3: Configure the Application Directory properties

The **second step** in the cell configuration process is to edit the **fr_application_directory.properties** file for edu.harvard.i2b2.ontology. During this step you need to specify a location for the application properties directory. This location can be anything you desire but it must be a directory path that the Windows or Linux user has been granted permission to access.

Steps to update fr_application_directory.properties

1. At the command prompt type the following:

Linux Command

```
open YOUR_I2B2_SRC_DIR/edu.harvard.i2b2.fr/etc/spring/fr_application_directory.properties
```

Windows Command

```
YOUR_I2B2_SRC_DIR/edu.harvard.i2b2.fr/etc/spring/fr_application_directory.properties
```

EXAMPLES:

Linux Command: open /opt/i2b2/edu.harvard.i2b2.fr/etc/spring/fr_application_directory.properties

Windows Command: C:\opt\i2b2\edu.harvard.i2b2.fr\etc\spring\fr_application_directory.properties

2. The **fr_application_directory.properties** file will open. Set the following properties to reflect your environment:

Application properties for FR Cell

```
edu.harvard.i2b2.fr.applicationdir=/ YOUR\_JBOSS\_HOME\_DIR/standalone/configuration/frapp
```

3. Save the changes and close the file.