

10.4.3.2 Project Management Cell Properties for CRC Loader

Step 5: CRC Loader properties: Configure PM cell properties

In order for the **CRC loader** to communicate with the *Project Management (PM) Cell* the following properties need to be modified to reflect your environment.

1. In the **edu.harvard.i2b2.crc.loader.properties** file scroll to the section called **File Management Cell**.
2. Edit the **edu.harvard.i2b2.crc.loader.pm.fr.url** property to reflect the location of the PM cell in your environment.



Important

When you edit the **edu.harvard.i2b2.crc.loader.ws.pm.url** property with the location of your PM Cell it is *extremely important* that you only edit the **hostname** (*localhost*) and the **port** (*9090*). The remainder of the URL is required as it is written and should not be changed.

Project Management Cell

```
edu.harvard.i2b2.crc.loader.ws.pm.url=http://localhost:9090/i2b2/services/PMService/getServices
# Flag to bypass project management cell
edu.harvard.i2b2.crc.loader.ws.pm.bypass=false
edu.harvard.i2b2.crc.loader.ws.pm.bypass.roleADMIN
edu.harvard.i2b2.crc.loader.ws.pm.bypass.projectDemo
```

3. Save your changes but do not close the file. You will be continuing to edit the file in the next few sections.