

## 9.4.2 Configure Ontology Application Directory Properties

### Step 3: Configure the Application Directory properties

The **second step** in the cell configuration process is to edit the **ontology\_application\_directory.properties** file for edu.harvard.i2b2.ontology. During this step you need to specify a location for the application properties directory. This location can be anything you desire but it must be a directory path that the Windows or Linux user has been granted permission to access.

#### Steps to update ontology\_application\_directory.properties

1. At the command prompt type the following:

##### Linux Command

```
open YOUR_I2B2_SRC_DIR/edu.harvard.i2b2.ontology/etc/spring/ontology_application_directory.properties
```

##### Windows Command

```
YOUR_I2B2_SRC_DIR\edu.harvard.i2b2.ontology\etc\spring\ontology_application_directory.properties
```

#### EXAMPLES:

**Linux Command:** open /opt/i2b2/edu.harvard.i2b2.ontology/etc/spring/ontology\_application\_directory.properties

**Windows Command:** C:\opt\i2b2\edu.harvard.i2b2.ontology\etc\spring\ontology\_application\_directory.properties

2. The **ontology\_application\_directory.properties** file will open. Set the following properties to reflect your environment:

##### Application properties for ONT Cell

```
edu.harvard.i2b2.ontology.applicationdir=/YOUR_JBOSS_HOME_DIR/standalone/configuration/ontologyapp
```

3. Save the changes and close the file.