

12.4.3 Configure the FR Properties

File Repository Properties Configuration

The **edu.harvard.i2b2.fr.properties** file contains a number of properties that need to be modified with the variables that are specific to your environment. The File Repository Cell needs these properties to deploy correctly and to set required parameters.

Step 4: PM Cell Properties

In order for the File Repository Cell to communication with the PM Cell the following properties need to be modified to reflect you environment.

1. At the command prompt type the following:

Linux Command

```
open YOUR_I2B2_SRC_DIR/edu.harvard.i2b2.fr/etc/spring/edu.harvard.i2b2.fr.properties
```

Windows Command

```
YOUR_I2B2_SRC_DIR/edu.harvard.i2b2.fr/etc/spring/edu.harvard.i2b2.fr.properties
```

EXAMPLES:

Linux Command:

```
open /opt/i2b2/edu.harvard.i2b2.fr/etc/spring/edu.harvard.i2b2.fr.properties
```

Windows Command:

```
C:\opt\i2b2\edu.harvard.i2b2.fr/etc/spring/edu.harvard.i2b2.fr.properties
```

2. The **edu.harvard.i2b2.fr.properties** file will open.
3. Scroll to the section called **Project Management Cell**.
4. Edit the **edu.harvard.i2b2.fr.ws.pm.url** property to reflect the location of the PM cell in your environment.



Important

When you edit the **edu.harvard.i2b2.fr.ws.pm.url** property with the location of your PM Cell it is ***extremely important*** that you only edit the **hostname** (*localhost*) and the **port** (*9090*). The remainder of the URL is required as it is written and should not be changed.

Project Management Cell

```
edu.harvard.i2b2.fr.ws.pm.url=http://localhost:9090/i2b2/services/PMService/getServices
edu.harvard.i2b2.fr.ws.pm.webServiceMethod=REST
# Flag to bypass project management cell
edu.harvard.i2b2.fr.ws.pm.bypass=false
edu.harvard.i2b2.fr.ws.pm.bypass.role=ADMIN
edu.harvard.i2b2.fr.ws.pm.bypass.project=Demo
```

5. Save your changes and close the file.