WORK QRY.xsd

WORK_QRY.xsd

<request></request>	Container for request information

<folders></folders>	Container list of folders returned in a response

<folder></folder>	Container for a folder returned in a response; an object that holds information from rows in a WORKPLACE table.
<name></name>	The name of the workplace item.
<index></index>	A " table code\unique index" pair. Example: \\i2b2\1 In the above example, "i2b2" equates to the table code and a unique index of "1".
<parentindex></parentindex>	The index of the parent of this workplace item.
<visualattributes></visualattributes>	Three character string that indicates the graphical representation of the term. Example: String XYZ, where X can be "C" (container), "F" (folder), "L" (leaf), "M" (multi) Y can be "A" (active), "I" (inactive), "H" (hidden) Z can be "O" (open) or null
<tooltip></tooltip>	A tooltip that is associated with the workplace item.
<groupid></groupid>	The project or group ID associated with the workplace item.
<shareid></shareid>	Indicates whether or not the workplace item is shared (Y/N).
<statuscd></statuscd>	Indicates the status of the workplace item ("D" = deleted).
<userid></userid>	The user ID of the originator of the workplace item.
<workxmlschema></workxmlschema>	The schema associated with <workxml>.</workxml>
<workxmli2b2type></workxmli2b2type>	The i2b2 type associated with the drag and drop XML.