

QT_QUERY_RESULT_INSTANCE

The result status for each setfinder query is stored in the QT_QUERY_RESULT_INSTANCE table

QT_QUERY_RESULT_INSTANCE			
Key	Column Name	Column Definition	Nullable? (Default = YES)
PK	RESULT_INSTANCE_ID	Unique id for the query	NO
FK	QUERY_INSTANCE_ID	Foreign key reference to the QT_QUERY_INSTANCE table	NO
FK	RESULT_TYPE_ID	Foreign key reference to the QT_QUERY_RESULT_TYPE table	NO
	SET_SIZE	The size of the results; the size of the patient set or encounter set. The value is based on the user role; an obfuscated value may be stored in this column.	YES
	START_DATE	The timestamp for the start of each query result generated.	NO
	END_DATE	The timestamp for the end of each query result generated.	YES
	DELETE_FLAG	A flag to denote if this result instance is deleted (Y / N).	NO
FK	STATUS_TYPE_ID	Foreign key reference to the QT_STATUS_TYPE table.	NO
	MESSAGE	To store the query error message, warning, etc.	YES
	DESCRIPTION	The description displayed to the user in the client (i2b2 Web client and Workbench)	YES
	REAL_SET_SIZE	The real set size. Unlike the SET_SIZE this column does NOT store obfuscated results.	YES
	OBFUSC_METHOD	Method used to obfuscated the results, default is OBSUBTOTAL	YES