

Storing Encounter Collections

An encounter collection (or set) may be dragged from the *Previous Query* view. The namespace for the schema that defines the Encounter Collection XML content is <http://www.i2b2.org/xsd/cell/crc/psm/1.1/>

The plugin_drag_drop XML message for an encounter collection is as follows:

```
<ns5:plugin_drag_drop
xmlns:ns5="http://www.i2b2.org/xsd/hive/plugin/"
xmlns:ns2="http://www.i2b2.org/xsd/hive/msg/1.1/"
xmlns:ns3="http://www.i2b2.org/xsd/cell/work/1.1/"
xmlns:ns4="http://www.i2b2.org/xsd/cell/pm/1.1/"
xmlns:tns="http://ws.workplace.i2b2.harvard.edu">
  <ns4:query_result_instance
xmlns:ns4="http://www.i2b2.org/xsd/cell/crc/psm/1.1/">
    <result_instance_id>322</result_instance_id>
    <query_instance_id>322</query_instance_id>
    <description>Encounter Set - 295 encounters</description>
    <query_result_type>
      <result_type_id>2</result_type_id>
      <name>PATIENT_ENCOUNTER_SET</name>
      <display_type>LIST</display_type>
      <visual_attribute_type>LA</visual_attribute_type>
      <description>Event list</description>
    </query_result_type>
    <set_size>295</set_size>
    <obfuscate_method />
    <start_date>2010-11-29T10:16:09.003-05:00</start_date>
    <end_date>2010-11-29T10:16:12.030-05:00</end_date>
    <message />
    <query_status_type>
      <status_type_id>3</status_type_id>
      <name>FINISHED</name>
      <description>FINISHED</description>
    </query_status_type>
  </ns4:query_result_instance>
</ns5:plugin_drag_drop>
```