

2.2.3 Configuration

The admin is pre-configured for a **local host** domain of **i2b2demo**. The steps in this section will walk you through how to configure the Admin to a different domain or host.

Steps to update domain and host



WARNING

Make sure you are editing the files in your **web server directory** and *not* the ones that reside in *YOUR_I2B2_SRC_DIR*.

1. Go to the **admin folder** in your **web server directory**.

Examples:

Linux: /var/www/html

Windows: C:\inetpub\wwwroot

2. Open the **i2b2_config_data.js** file.
3. Edit or add additional domains for your environment.
4. It is very important you add the line that says "adminOnly: true" to the file. (See the code block below.) This causes the web client to start in admin mode.



Important

- If you are installing the i2b2 demo environment do not edit the domain "i2b2demo" except to update the *urlCellPM* with your host and port for the location of the PM Cell.
- If you are setting up your own i2b2 environment with test or production data then you can copy the domain section and edit it to reflect your environment.

i2b2_config_data.js

```
{
  urlProxy: "index.php",
  urlFramework: "js-i2b2/",
  //-----
  // THESE ARE ALL THE DOMAINS A USER CAN LOGIN TO
  lstDomains: [
    { domain: "i2b2demo",
      name: "i2b2demo",
      urlCellPM: "http://localhost:9090/i2b2/services/PMService/",
      allowAnalysis: true,
      adminOnly: true,
      debug: false
    }
  ]
  //-----
}
```

4. Save the changes and close the file.

