

11.4.2 Configure the Workplace Application Directory Properties

Step 3: Configure the Application Directory properties

The **third step** in the cell configuration process is to edit the **workplace_application_directory.properties** file for edu.harvard.i2b2.workplace. During this step you need to specify a location for the application properties directory. This location can be anything you desire but it must be a directory path that your Windows or Linux user has been granted permission to access.

Steps to update workplace_application_directory.properties

1. At the command prompt type the following:

Linux Command

```
open YOUR_I2B2_SRC_DIR/edu.harvard.i2b2.workplace/etc/spring/workplace_application_directory.properties
```

Windows Command

```
YOUR_I2B2_SRC_DIR/edu.harvard.i2b2.workplace\etc\spring\workplace_application_directory.properties
```

EXAMPLES:

Linux Command: open /opt/i2b2/edu.harvard.i2b2.workplace/etc/spring/workplace_application_directory.properties

Windows Command: C:\opt\i2b2\edu.harvard.i2b2.workplace\etc\spring\workplace_application_directory.properties

2. The **workplace_application_directory.properties** file will open. Set the following properties to reflect your environment:

Application properties for WORK Cell

```
edu.harvard.i2b2.workplace.applicationdir=/YOUR_JBOSS_HOME_DIR/standalone/configuration/workplaceapp
```

3. Save the changes and close the file.