

2.4.5 System Environment Variables

Set System Environment Variables

In order to ease the installation process we recommend you set the following environment variables. The commands given throughout the document are based on the following environment variables defined on your machine.

Environment Variables

JAVA_HOME=[the location of your Java JDK directory](#)
JBOSS_HOME=[the location of your Wildfly directory](#)
ANT_HOME=[the location of your Ant directory](#)
PATH=[add the path for your Java's bin folder and Ant bin folder.](#)
export [Your Java, Wildfly and Ant Home Directories](#)



Note

Changes to the system PATH variable are not necessary for servers running Windows. JAVA_HOME, JBOSS_HOME and ANT_HOME still need to be set.

Also the need to *export* the new variables is only required on Linux machines; it is not applicable to Windows.

Example Settings for Linux Machine

Environment Variables

```
JAVA_HOME=/usr/java/default
JBOSS_HOME=/opt/wildfly-17.0.0.Final
ANT_HOME=/opt/apache-ant-1.9.6
PATH=$PATH:$ANT_HOME/bin:$JAVA_HOME/bin
export JAVA_HOME
export JBOSS_HOME
export ANT_HOME
```

Please proceed to the section called ***Set Variables on Linux Machine*** if you are unfamiliar with how to set the above system variables on your Linux server.

Example Settings for Windows Server

Environment Variables

```
JAVA_HOME=C:\Program Files\Java\jdk1.8.0_121
JBOSS_HOME=c:\opt\wildfly-17.0.0.Final
ANT_HOME=c:\opt\apache-ant-1.9.6
PATH=%PATH;%ANT_HOME\bin;%JAVA_HOME\bin
```

Please proceed to the section called ***Set Variables on Windows Machine*** if you are unfamiliar with how to set the above system variables on your Windows server.