Upgrade to latest version (1.8.0)

Version Information

Current Version:	1.8.0
Release Date:	December 2023
License:	Mozilla 2 Open Source License

Download

Description	i2b2 Released Version	Minimum Version Required	Download Link	Requirements
Files to upgrade the i2b2 server to 1.8.0	1.8.0	1.7.09c	i2b2core-upgrade-1.8.0.zip (downloadable)	See Technical Details section on the i2b2 Upgrades page.
Files to upgrade the i2b2 db instance to 1.8.0	1.8.0	1.7.09c	i2b2 data-source1.8.0.zip	
Files to upgrade the webclient	1.8.0		i2b2webclient-source180.zip	

Notes

() If you are running your application on JBoss, please upgrade to Wildfly before proceeding with the upgrade

Upgrade Instructions

Below are Step-by-Step Instructions after you have upgraded to Wildfly.

Initial Steps:

- Download the binary upgrade distribution from i2b2core-upgrade-180.zip
- Extract the download file i2b2core-upgrade-180.zip to a folder outside of your existing i2b2 installation folder

Then, follow the steps below to upgrade i2b2 server, database instance and the webclient.

Steps to Upgrade i2b2 Server

In the following instructions the variable { version } refers to your version of Wildfly installed. We now support Wildfly 17 version.

Stop WildFly

Linux Example

\$ /opt/wildfly-{version}.Final/bin/jboss-cli.sh --connect command=:shutdown

Windows Standalone Example

> \opt\wildfly-{version}.Final\bin\standalone stop

Backup existing deployment directory containing i2b2.war file

Linux

2

On Linux, move the /opt/wildfly-{version}. Final/standalone/deployments/ and save it to a different location outside of /opt/wildfly-{version}. Final/

Windows

On Windows, move the c:\opt\wildfly-{version}.Final\standalone\deployments\ and save it to a different location outside of c:\opt\wildfly-{version}.Final\

Upgrade deployments folder

Copy all the files from the extracted downloaded deployment folder into your existing WildFly standalone/deployments directory.

Example your deployments folder: /opt/<wildfly-17.0.0.Final and above version>/standalone/deployments/

Example extracted deployments folder: i2b2core-upgrade-180\i2b2\deployments

The folder includes the upgraded war file and upgraded jdbc driver files.

Ū

Update datasource (*-ds.xml) files

In your deployment directory, copy *-ds.xml files from the backup folder to wildfly-17.0.#.Final/standalone/deployments

Edit the following files crc-ds.xml, ont-ds.xml, pm-ds.xml, work-ds.xml

Replace ALL the <driver>{something}.jar</driver> with latest drivers as below

Oracle	SQL Server	PostgreSQL
<driver>ojdbc8.jar</driver>	<pre><driver>mssql-jdbc9.2.0jre8.jar</driver></pre>	<driver>postgresql42.3.2.jar</driver>

5

Migrate cell properties to 1.8.0 if needed. In 1.7.12, cell properties have been moved to the database, in a table called hive_cell_params. If any cell properties were previously changed, they will need to be manually updated in the database. After this, the properties files can be deleted to prevent confusion.

More documentation on setting cell properties is available at this page. Most commonly, the AGG_SERVICE_ACCOUNT password will need to be updated. Generally, the cell URLs do not need to be configured anymore, as the hostname and port is now auto-detected.

Properties files are stored at */opt/wildfly-{version}.Final/standalone/configuration/* on **Linux** and c:*lopt/wildfly-{version}. Final/standalone/configuration* on **Windows**. The table can be edited with a SQL editor in hive_cell_params.

Steps to Upgrade i2b2 database

Steps to perform db upgrade:

- · Backup your existing data folder
- Copy all the folders created by extracting the latest version into your existing data Upgrade folder. This will replace existing Crcdata, Hivedata, Metadata, PMdata folders. Example: Downloads\i2b2core-upgrade-180\i2b2\data to C: \opt\edu.harvard.i2b2.data\Release_1-8\Upgrade\.
- Copy the db.properties files from your back up into the respective locations (namely Crcdata, Hivedata, Metadata, PMdata)
- Open the command prompt and navigate to each cell folder and run the following upgrade ant commands on your i2b2 database instance, where {db} can be Oracle, sqlserver or postgresql.
 Alternative to above Step, you can run individual SQL scripts on your db instance in place of ant commands.
- In datafolder\Release_1-8\Upgrade\ run the ant commands under each individual cell folder as below

Upgrade	Upgrade to Latest build
From	
Build	

4

1.7.09c	In the Crcdata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7-09c upgrade_tables_release_1-7-10 upgrade_tables_release_1-7-11 upgrade_tables_release_1-7-12a
	In the Hivedata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7- 11 upgrade_tables_release_1-7-12a
	In the Metadata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7- 10 upgrade_tables_release_1-7-12a
	In the Pmdata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7-09c
1.7.10	In the Crcdata folder run the following ant command: ant -f data_build.xml upgrade_table_release_1-7-10 upgrade_tables_release_1-7-11 upgrade_tables_release_1-7-12a
	In the Hivedata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7-11 upgrade_tables_release_1-7-12a
	In the Metadata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7-10 upgrade_tables_release_1-7-12a
1.7.11	In the Crcdata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7- 11 upgrade_table_release_1-7-12a
	In the Hivedata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7- 11 upgrade_tables_release_1-7-12a
	In the Metadata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7-12a
1.7.12a	In the Crcdata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7-12a
	In the Hivedata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7-12a
	In the Metadata folder run the following ant command: ant -f data_build.xml upgrade_tables_release_1-7-12a
1.7.13	For Oracle and Postgres, no database upgrade is required. If using SQL Server, reload the following stored procedures:
	In the Metadata folder run the following ant command: ant -f data_build.xml rebuild_procedures

(i) HIVE_CELL_PARAMS configuration

Check HIVE_CELL_PARAMS table is updated with cell properties parameters as detailed here

Steps to Upgrade i2b2 Webclient

Backup existing webclient folder to a different location outside of your current webclient installation folder

Install new webclient

• Extract the i2b2webclient-180.zip

- Replace your existing webclient folder on your web server with the extracted new webclient folder
- i2b2_config_data.js has been renamed to i2b2_config_domain.json. Edit the i2b2_config_domain.json using your existing i2b2_config_data.js from your backed up web directory. Details are provided here

Backup your entire webclient folder before proceeding with webclient upgrade

Start WildFly

You can either run WildFly standalone or as a service.

Linux Standalone Example

\$ /opt/wildfly-{version}.Final/bin/standalone.sh -b 0.0.0.0 &

Windows Standalone Example

> \opt\wildfly-{version}.Final\bin\standalone start

Verify Your Upgrade

O Test Webclient

Navigate to your local i2b2 Web Client in your preferred browser and verify you are able to log on and perform standard i2b2 functions. (e.g. Run queries, retrieve previous queries, view breakdowns, etc.)